

**Continental**   
The Future in Motion



# HSR2

## Heavy Steer Regional

Continental offers the right tire for every application and type of terrain. Whether you need to take the highway, regional roads, city traffic or even venture off road, our premium tires for trucks and buses are engineered to suit your specific application needs.


Commercial Vehicle Tires | [www.continental-truck.com](http://www.continental-truck.com)

Scan code or visit  
[www.continental-truck.com](http://www.continental-truck.com)  
for the most up to date  
product information.





## Heavy Steer Regional



- 23/32" deep improved cut and chip resistant tread compound for optimal performance.
- Patented groove geometry for better resistance to cracking and tearing.
- Protective curb rib for high scrub applications.
- Patented innovative groove technology leads to minimum stone retention, extending casing life.



### Applications

Regional hauling and on/off road, all-position.

### Segments

- Goods
- People
- Construction

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													LBS (KG)	PSI (KPa)	LBS (KG)	PSI (KPa)
<b>TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS</b>																
10R22.5	G	05686570000	20	75	18.8 (478)	40.0 (1016)	10.0 (254)	10.8 (274)	750,6.75,8.25	11.4 (290)	518 (322)	105 (48)	5675 (2575)	115 (790)	5355 (2430)	115 (790)
11R22.5*	G	05686300000	23	75	19.4 (493)	41.6 (1057)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	498 (309)	121 (55)	6175 (2800)	105 (720)	5840 (2650)	105 (720)
11R22.5*	H	05686310000	23	75	19.4 (493)	41.6 (1057)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	498 (309)	122 (55)	6610 (3000)	120 (830)	6005 (2725)	120 (830)
12R22.5	H	05120880000	23	75	20.1 (511)	42.9 (1090)	11.4 (290)	12.1 (306)	9.00, 8.25	13.5 (343)	482 (300)	133 (60)	7390 (3350)	120 (830)	6780 (3075)	120 (830)
275/80R22.5*	G	05686340000	23	75	18.7 (475)	40.0 (1016)	11.1 (282)	12.6 (320)	8.25	12.5 (318)	518 (322)	116 (53)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
275/80R22.5*	H	05686350000	23	75	18.6 (472)	40.0 (1016)	11.1 (282)	12.6 (320)	8.25	12.5 (318)	518 (322)	117 (53)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
11R24.5*	G	05686320000	23	75	20.4 (518)	43.5 (1105)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	476 (296)	129 (59)	6610 (3000)	105 (720)	6005 (2725)	105 (720)
11R24.5*	H	05686330000	23	75	20.4 (518)	43.5 (1105)	11.1 (282)	12.0 (305)	8.25	12.5 (318)	476 (296)	130 (59)	7160 (3250)	120 (830)	6610 (3000)	120 (830)
285/75R24.5*	G	05686360000	23	75	19.4 (493)	41.3 (1049)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	501 (311)	121 (55)	6175 (2800)	110 (760)	5675 (2575)	110 (760)
285/75R24.5*	H	05687020000	23	75	19.4 (493)	41.3 (1049)	10.7 (272)	12.1 (307)	8.25	12.5 (318)	501 (311)	121 (55)	6780 (3075)	120 (830)	6175 (2800)	120 (830)

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. \* - ECE Certified. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

