

Continental 
The Future in Motion



Conti Hybrid HS3 - 19.5"

Hybrid Steer

Continental offers the right tire for every application and type of terrain. Whether you need to take the highway, regional roads, city traffic or even venture off road, our premium tires for trucks and buses are engineered to suit your specific application needs.

Commercial Vehicle Tires | www.continental-truck.com

Scan code or visit
www.continental-truck.com
for the most up to date
product information.




Conti Hybrid HS3 - 19.5"

Mileage

Pocket Sipes



Hybrid Steer



- Two-layer tread construction combines high mileage performance in the cap compound with significant rolling resistance improvements in the base compound.
- Narrowed groove widths result in increased pattern volume which improves wear resistance to guarantee high mileage performance.
- Pocket sipe technology with full-depth sipes to enhance water displacement and improve wet performance over the life of the tire.



Applications

Long haul/Regional over the highway all-position use.

Segment

- Goods
- People

Tire Size	Load Range	Article Number	Tread Depth (32nds)	Max Speed (MPH)#	Static Loaded Radius IN (MM)	Overall Inflated Diameter IN (MM)	Overall Inflated Width IN (MM)	Loaded Section Width IN (MM)	Approved Rim(s)	Minimum Dual Spacing IN (MM)	Revs Per Mile (KM)	Tire Weight LB (KG)	MAX. LOAD@INFLATION			
													LBS PSI (KG KPa)	LBS PSI (KG KPa)		
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
225/70R19.5	G	05111140000	16	87	14.9 (378)	31.9 (810)	8.6 (218)	9.4 (239)	6.00, 6.75	10.0 (254)	649 (403)	62 (28)	3970 (1800)	110 (760)	3750 (1700)	110 (760)
245/70R19.5	H	05111130000	16	81	15.2 (386)	32.8 (833)	9.5 (241)	10.3 (262)	6.75, 7.50	11.0 (279)	631 (392)	75 (34)	4940 (2240)	120 (830)	4675 (2120)	120 (830)
265/70R19.5	H	05121160000	17	81	15.8 (401)	34.7 (881)	10.3 (262)	10.7 (272)	7.50, 6.75, 8.25	11.2 (286)	612 (380)	82 (37)	5510 (2500)	115 (790)	5205 (2360)	115 (790)
285/70R19.5	H	05121130000	18	81	16.2 (412)	35.9 (911)	11.1 (283)	11.6 (294)	8.25, 7.50, 9.00	12.5 (318)	590 (366)	93 (42)	6610 (3000)	125 (860)	6175 (2800)	125 (860)
305/70R19.5*	J	05121140000	19	81	16.7 (424)	36.3 (923)	11.8 (300)	12.7 (323)	8.25, 9.00	13.2 (335)	572 (355)	99 (45)	6940 (3150)	125 (860)	6395 (2900)	125 (860)

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified. # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.

