



TIRES FOR TRUCK AND BUS





NORDEX - great tires **NXD201**

- › Drive position tyre.
- › Provides maximum grip on mixed surfaces and offers optimal distribution of impacts to protect the tyre and improve comfort.
- › Good for highway use and some off-road service.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
11R22.5	148/145M	18	20.5 mm
12R22.5	152/148M	18	22.0 mm
13R22.5	154/150K	18	22.0 mm
295/80R22.5	152/148M	18	20.5 mm
315/80R22.5	156/154M	20	22.0 mm



NORDEX - great tires **NXD202**

- › Drive position tyre, but can be used in trailer position on rough surfaces.
- › Provides optimal overall grip on all surfaces, combining center block strength with large shoulder blocks for shock absorbtion.
- › Good for mixed road service.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
315/80R22.5	156/154M	20	19.5 mm





NXD203

- › Drive position, but can be used in all positions strictly off-road.
- › Provides maximal impact resistance on rough surfaces and optimal grip on rocks, dirt, and mud.
- › Good for off-road service and mainly bad road usage.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
12R22.5	152/149J	18	25.0 mm



NXD204

- › Drive position tyre, but can be used in all positions strictly off-road.
- › Provides maximal impact resistance on rough surfaces and optimal grip on rocks, dirt, and mud.
- › Good for off-road service and mainly bad road usage.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
12.00R20	156/153F	20	21.5 mm



NXD205

- › Drive position tyre.
- › Provides good grip, low rolling resistance, and a high level of comfort.
- › Optimal for highway use and slight off-road usage.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
11R22.5	146/143M	16	21,5 mm
11R24.5	149/146M	16	21,5 mm
295/75R22.5	146/143L	16	21,5 mm
285/75R24.5	147/144L	16	21,5 mm





NXS101

- › Steering position tyre, but can also be used in trailer position on highway and slight off-road usage.
- › Increased siping offer sideways stability and optimal turning grip on most surfaces.
- › Good for highway and off-road service.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
315/80R22.5	156/154M	20	15.5 mm



NXS102

- › Steering position tyre.
- › Provides improved grip and stability in all directions, and offers good shock absorption and high comfort.
- › Good for highway use and some off-road service.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
11R22.5	148/145M	18	15.0 mm
12R22.5	152/148M	18	15.5 mm
295/80R22.5	152/148M	18	15.0 mm



NXS103

- › Steering position tyre, but can be used in trailer position off-road.
- › Increased tread depth and strong center blocks offer maximized resistance to impact and heat, and good stability.
- › Good for mixed highway and off-road service.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
12R22.5	152/148M	18	17.8 mm





NXS104

- › Steering position tyre.
- › Offers minimal rolling resistance, low fuel consumption, and a high level of comfort.
- › Optimal for use on highway and city roads..



SIZE	LI/SR	PLY RATING	TREAD DEPTH
11R22.5	146/143M	16	14,5 mm
11R24.5	149/146M	16	14,5 mm
295/75R22.5	146/143L	16	14,5 mm
285/75R24.5	147/144L	16	14,5 mm

NXS105

- › Steering position tyre, but can be used in all positions on good surfaces.
- › Strong center blocks offer maximum impact resistance and good grip when turning.
- › Good for highway and off-road service.



SIZE	LI/SR	PLY RATING	TREAD DEPTH
7.50R16	122/118L	14	12.5 mm
8.25R16	128/124L	16	13.0 mm
10.00R20	149/146K	18	16.5 mm
11.00R20	152/149K	18	17.0 mm
12.00R20	156/153K	20	17.5 mm



NORDEX - great tires **NXT301**

- › Trailer position tyre. Only mount as single position.
- › Provides optimal flexibility and direction stability.
- › For highway use and light off-road use only.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
385/65R22.5	160K	20	16.0 mm



NORDEX - great tires **NXA401**

- › All position tyre.
- › Provides high flexibility, maximum sideways stability, and good grip on most surfaces.
- › Good for highway use and some off-road usage.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
13R22.5	154/150K	18	15.5 mm





NXA402

- › All position tyre.
- › Zig-zag pattern offers both traction and directional stability.
- › Good for mainly highway and slight off-road use.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
7.50R16	122/118L	14	12,0 mm
8.25R16	128/124L	16	12,0 mm
8.25R20	139/137K	16	12,0 mm
9.00R20	144/142K	16	15,5 mm
10.00R20	149/146K	18	17,0 mm
11.00R20	152/149K	18	17,0 mm
12.00R20	156/153K	20	17,5 mm
12.00R24	160/157K	20	16,0 mm
315/80R22.5	156/154M	20	15,8 mm



NXA403

- › All position tyre.
- › Strong shoulders and center blocks offer maximized direction stability and impact resistance.
- › Good for mixed highway and off-road service.

SIZE	LI/SR	PLY RATING	TREAD DEPTH
12.00R24	160/157K	20	15.8 mm





Distributed by: