

**VKT** E-2,G-2,L-2

**V-STEEL K-TRACTION**



The V-STEEL K-TRACTION radial tire features a heavy-duty, all steel radial traction design for graders, loaders and earthmovers.

**SPECIALIZED FEATURES**

- Directional tread pattern
- Cut resistant tread design for even wear
- Excellent traction and flotation

# VKT E-2,G-2,L-2

V-STEEL K-TRACTION



CATEGORY	SIZE	PLY/STAR RATING	COMPOUND/ CONSTRUCTION	TRA	ARTICLE #	AVG. WT.	OTD (32ND)	OVERALL DIAMETER	OVERALL WIDTH
SMALL TUBE TYPE	14.00R24 +	3*	E2A	E-2	419745	330	32	53.2	15.4
	14.00R24 ‡	1*	G2A	G-2	263354	310	32	53.2	14.6
SMALL TUBELESS	14.00R24 ‡	3*	E2A	E-2	263346	340	32	53.2	15.4
	16.00R24 ‡	1*	G2A	G-2	284971	410	36	58.0	16.5
	15.5R25	1*	D2A	L-2	263370	280	30	50.2	15.4
	17.5R25	1*	D2A	L-2	263389	340	34	52.7	17.3
	17.5R25	1*	EG2	E-2	296341	320	34	52.9	17.3
	18.00R25	2*	E1A	E-2	261335	610	39	63.4	20.1
	20.5R25	1*	D2A	L-2	263397	450	38	57.9	20.9
	23.5R25	1*	D2A	L-2	263400	690	42	63.1	24.1
	23.5R25	2*	E1A	E-2	261351	650	42	63.1	24.1
	25/65R25	2*	E2A LS	E-2	272558	590	38	58.5	25.0
	LARGE TUBELESS	26.5R25	1*	D2A	L-2	275611	910	49	68.2
26.5R25		2*	E1A	E-2	275638	860	49	68.2	26.7
29.5R25		2*	E1A	E-2	275646	1,140	55	73.3	30.0
29.5R29		2*	E1A	E-2	275654	1,250	55	77.1	30.1
29.5R29		2*	E2A LS	E-2	276235	1,250	55	77.1	30.1
37.5R39		2*	E1A	E-2	419915	2,660	64	99.4	38.7

+ For use on Flat Base Rim.

‡ For use on semi drop center rim only, not for use on Flat Base Rim.

**BRIDGESTONE**  
OFF THE ROAD TIRES