

Continental 
The Future in Motion



HTC1

Heavy Trailer Construction

Continental offers the right tire for every application and type of terrain. Whether you need to take the highway, regional roads, city traffic or even venture off road, our premium tires for trucks and buses are engineered to suit your specific application needs.





Applications

Wide base, all-position fitment for on/off, mixed service applications.

Segment

Construction

Heavy Trailer Construction

- Aggressive multi-service, all-position tread pattern provides excellent traction.
- Cut and tear resistant tread compound for long tread life in on/off road conditions.
- Rugged casing design resists casing penetrations and damage, allowing multiple retreads.
- Outstanding self-cleaning properties ensure a long service life.

ContiTread™

| TREAD DEPTH | |
|-------------|--------|
| TREAD WIDTH | 24/32" |
| | 320 |
| | 350 |



Reference the CLC Data Guide for further information.

| Tire Size | Load Range | Article Number | Tread Depth (32nds) | Max Speed (MPH)# | Static Loaded Radius IN (MM) | Overall Inflated Diameter IN (MM) | Overall Inflated Width IN (MM) | Loaded Section Width IN (MM) | Approved Rim(s) | Minimum Dual Spacing IN (MM) | Revs Per Mile (KM) | Tire Weight LB (KG) | MAX. LOAD@INFLATION | | |
|---|------------|----------------|---------------------|------------------|------------------------------|-----------------------------------|--------------------------------|------------------------------|---------------------|------------------------------|--------------------|---------------------|---------------------|------------------|----|
| | | | | | | | | | | | | | LBS PSI (KG KPa) | LBS PSI (KG KPa) | |
| TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS | | | | | | | | | | | | | | | |
| 385/65R22.5 * | L | 05350090000 | 23 | 68 | 195 (495) | 420 (1067) | 14.7 (373) | 16.2 (411) | 12.25, 11.75 | NA (306) | 493 (76) | 167 (76) | 9920 (4500) | 130 (900) | NA |
| 425/65R22.5 | L | 05350100000 | 24 | 68 | 20.4 (517) | 44.5 (1130) | 16.6 (422) | 18.0 (457) | 12.25, 13.00, 14.00 | NA (289) | 465 (83) | 183 (83) | 11,400 (5150) | 120 (830) | NA |
| 445/65R22.5 * | L | 05350190000 | 23 | 68 | 20.6 (524) | 46.2 (1174) | 17.7 (450) | 19.1 (485) | 14.00, 13.00 | NA (287) | 462 (84) | 185 (84) | 12,800 (5800) | 120 (830) | NA |

Note - Rim listed first is the measuring rim. Minimum Dual Spacing calculated without chains. * - ECE Certified # - Exceeding the lawful speed limit is neither recommended nor endorsed. Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly. Continental Tire the Americas, LLC reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturers load and inflation limits. Never exceed rim manufacturers limits without permission of component manufacturer.