

# SOLIDEAL PON 775

BY CAMSO



PRESS-ON  
TIRES



## DESIGNED FOR HIGH INTENSITY APPLICATIONS

Engineered to provide the best performance of heat resistance, energy efficiency and long-lasting life in high intensity applications.

[camso.co](http://camso.co)

## PERFORMANCE

INTENSITY



ENERGY SAVINGS



TIRE LIFE



**ROAD  
FREE  
COMPANY**


FORMERLY  
CAMOPLAST  
SOLIDEAL

PRESS-ON TIRES

# SOLIDEAL PON 775

BY CAMSO

TIRE SIZE <sup>(1)</sup>	TREAD	ACTUAL TIRE DIMENSIONS			LOAD CAPACITY <sup>(2)</sup> Counterbalanced lift trucks (lb.)					
	SMOOTH PON 775	OVERALL DIAMETER	OVERALL WIDTH	REPLACEMENT OVERALL DIAMETER <sup>(3)</sup>	6 mph		10 mph		16 mph	
		(in.)	(in.)	(in.)	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL	LOAD WHEEL	STEERING WHEEL
10 X 4 X 6 1/2	■	10	4	8.8	1720	1410	1530	1290	1245	1025
10 X 5 X 6 1/2	■	10	5	8.8	2225	1830	1995	1675	1620	1335
10 1/2 X 5 X 6 1/2	■	10.5	5	9.1	2360	1940	2115	1785	1720	1410
12 X 4 1/2 X 8	■	12	4.5	10.6	2295	1885	2050	1720	1665	1365
13 1/2 X 5 1/2 X 8	■	13.5	5.5	11.7	3330	2735	2965	2490	2415	1975
14 X 4 1/2 X 8	■	14	4.5	12	2580	2115	2305	1930	1875	1530
14 X 5 X 10	■	14	5	12.6	2945	2415	2635	2205	2140	1755
16 X 5 X 10 1/2	■	16	5	14.1	3330	2735	2965	2490	2415	1975
16 X 6 X 10 1/2	■	16	6	14.1	4210	3460	3770	3165	3065	2515
16 X 7 X 10 1/2	■	16	7	14.1	5125	4210	4565	3835	3715	3040
15 X 5 X 11 1/4	■	15	5	13.7	3065	2515	2735	2295	2225	1830
16 1/4 X 5 X 11 1/4	■	16.25	5	14.6	3375	2755	3000	2525	2435	1995
16 1/4 X 6 X 11 1/4	■	16.25	6	14.6	4235	3485	3780	3175	3075	2515
16 1/4 X 7 X 11 1/4	■	16.25	7	14.6	5125	4190	4540	3825	3705	3040
18 X 6 X 12 1/8	■	18	6	16	4630	3790	4125	3470	3360	2755
18 X 7 X 12 1/8	■	18	7	16	5620	4630	5025	4210	4090	3350
18 X 8 X 12 1/8	■	18	8	16	6615	5455	5910	4960	4805	3945
21 X 7 X 15	■	21	7	18.9	6340	5180	5645	4740	4595	3770
21 X 8 X 15	■	21	8	18.9	7440	6120	6670	5600	5410	4440
21 X 9 X 15	■	21	9	18.9	8600	7055	7660	6435	6240	5115
22 X 8 X 16	■	22	8	20	7715	6340	6900	5785	5610	4595
22 X 9 X 16	■	22	9	20	8930	7330	7935	6670	6460	5290
22 X 10 X 16	■	22	10	20	10085	8265	8995	7550	7310	5995
22 X 12 X 16	■	22	12	20	12400	10195	11090	9315	9015	7385
28 X 12 X 22	■	28	12	25.9	14860	12215	13270	11155	10805	8850



**WIDEST POSSIBLE FLAT FOOTPRINT**

- Reduces ground pressure to minimize heat build-up

**THERMALLY EFFICIENT CONSTRUCTION**

- Provides a cooler running tire and the best in class energy efficiency

**ABRASION-RESISTANT TREAD COMPOUND**

- Increases tire life

**UNIQUELY ENGINEERED SIDEWALL**

- Reduces heat build-up caused by stresses in the tread shoulders

**WEAR INDICATOR AND SAFETY LINE**

- Indicates when you should replace your tire

AUTHORIZED DISTRIBUTOR:

**Remarks**

(1) Tolerances on wheel diameter • Code designated sizes (in): nominal rim diameter +0.005"/-0" • Metric sizes (mm): h11 according to ISO/R286. Surface roughness Ra < 6.3 µm • Chamfer 5 mm wide @ 30°

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted.

(3) The tire is considered worn out when the outside diameter is equal or smaller than the replacement overall diameter.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.



Camso is the best of Camoplast and Solideal.  
To keep moving forward while staying true to our history,  
we're now the Road Free company.

[camsso.co](http://camsso.co)



FORMERLY  
CAMOPLAST  
SOLIDEAL