

SOLIDEAL PORTMASTER

BY CAMSO



INDUSTRIAL
PNEUMATIC



NO STRONGER BIAS TIRE.

The strongest and most durable bias tire in the world. Ideal on hard surfaces and in highly abrasive environments, its extremely deep tread increases service life while providing the strongest carcass and the most sidewall protection possible.

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



STABILITY



camsco.co



FORMERLY
CAMOPLAST
SOLIDEAL

SOLIDEAL PORTMASTER

BY CAMSO

| TIRE SIZE | PR | TUBE* & VALVE** | FLAP | RIM SIZE ⁽¹⁾ | | ACTUAL TIRE DIMENSIONS | | | | INFLATION PRESSURE (psi) | LOAD INDEX & SPEED SYMBOL | LOAD CAPACITY ⁽²⁾ Counterbalanced lift trucks (lbs) | | | |
|-----------|----|-----------------|--------|-------------------------|-------------|------------------------|--------------------|---------------------------|---------------------------|--------------------------|---------------------------|--|----------------|--------------|----------------|
| | | | | Recom- mended | Alternative | Overall diameter (in) | Section width (in) | Original tread depth (in) | Static loaded radius (in) | | | Up to 16 mph | | Up to 20 mph | |
| | | | | | | | | | | | | Load wheel | Steering wheel | Load wheel | Steering wheel |
| 12.00-20 | 20 | V3-02-14 | 200-20 | 8.50 | 8.00/10.00 | 45.0 | 12.6 | 2.2 | 20.3 | 145.0 | 175 A5 | 20350 | 15650 | 19565 | 14485 |
| 12.00-20 | 28 | V3-02-14 | 200-20 | 8.50 | 8.00/10.00 | 44.5 | 12.6 | 2.2 | 20.2 | 174.0 | 180 A5 | 22928 | 17637 | 22046 | 16402 |

MASSIVELY DEEP TREAD

- Provides longer service life on any surface



STRONGEST CARCASS AND SIDEWALL PROTECTION

- Prevents carcass damages due to cutting and sidewall impact

Remarks

(1) Consult tire and wheel manufacturer for confirmation of the suitability of the tire/rim combination particularly with regard to rim profile and wheel strength.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where tires are not used continuously at the load indicated by its Load Index and Speed Symbol. It does not refer to the length of time a vehicle is in use, but rather that there is a variation in load and/or speed.

* Tube size is identical to tire size.

** Table shows standard valves. Other valves on request.

NHS – Not for Highway Service: Tires primarily designed for use outside of public roads, but suitable for temporary/incidental use on public roads.

All tires come with tube and flap.

It is possible that certain items are not sold in your region.

Please contact your local sales contact to check tire availability in your region.

AUTHORIZED DISTRIBUTOR:



FORMERLY
CAMOPLAST
SOLIDEAL