

# SOLIDEAL RES 330

BY CAMSO



RESILIENT



## LONGEST LASTING TIRE IN THE INDUSTRY FOR LOW INTENSITY APPLICATIONS

Best-in-class tire for low intensity applications\*. A high performing tread rubber compound makes this tire a unique long lasting tire. Wide, aggressive tread with natural rubber compounds extends its life while resisting cutting and chunking. A steel-bead reinforced heel means the tire won't slip on the rim.

[camsco.co](http://camsco.co)

USAGE INTENSITY



PERFORMANCE



ENERGY SAVINGS



TIRE LIFE



COMFORT



FORMERLY  
CAMOPLAST  
SOLIDEAL

# RESILIENT

# SOLIDEAL RES 330

BY CAMSO

USAGE INTENSITY



TIRE SIZE	RIM SIZE <sup>(1)</sup>	HEEL		ACTUAL TIRE DIMENSIONS		WEARABLE HEIGHT	LOAD CAPACITY <sup>(2)</sup>	
				OVERALL DIAMETER	OVERALL WIDTH		Counterbalanced lift trucks (lbs)	
		NORMAL	QUICK				Load wheel	Steering wheel
		(in)	(in)	Up to 16 mph	Up to 16 mph			
5.00-8	3.00D-8	■	■	17.72	4.53	1.61	3120	2405
15x4 1/2-8 (125/75-8)	3.00D-8	■	■	14.57	4.57	1.08	2295	1765
16x6-8 (150/75-8)	4.33R-8	■	■	16.10	5.75	1.34	3295	2535
18x7-8 (180/70-8)	4.33R-8	■	■	17.52	5.83	1.57	4730	3640
6.00-9	4.00E-9	■	■	20.43	5.35	1.89	4155	3195
21x8-9 (200/75-9)	6.00E-9	■	■	20.28	7.13	1.87	6075	4675
200/50-10	6.50F-10	■	■	17.72	7.60	1.28	5445	4190
6.50-10	5.00F-10	■	■	22.28	6.02	2.05	5160	3970
23x9-10 (225/75-10)	6.50F-10	■	■	22.56	7.87	2.09	7595	5840
23x10-12 (250/60-12)	8.00G-12	■	■	22.72	9.21	1.77	8310	6395
27x10-12 (250/75-12)	8.00G-12	■	■	26.14	9.76	2.34	8600	6615
7.00-12	5.00S-12	■	■	25.39	6.50	2.19	6435	4940
28x9-15 (8.15-15 & 225/75-15)	7.00-15	■	■	26.81	8.31	1.91	7595	5840
355/45-15 (28x12.5-15)	9.75-15	■	■	26.57	11.50	1.87	12545	9645
355/65-15 (32x12.1-15)	9.75-15	■	■	31.93	12.20	2.76	17195	13230
250-15 (250/70-15)	7.00-15	■	■	27.83	8.35	2.07	10470	8045
250-15 (250/70-15)	7.50-15	■	■	27.83	8.35	2.07	10470	8045
300-15 (315/70-15)	8.00-15	■	■	31.81	9.84	2.74	12895	9920
7.00-15	5.50-15	■	■	28.39	7.28	2.17	7815	6010
7.50-15	6.50-15	■	■	29.25	7.99	2.30	8600	6615
8.25-15	6.50-15	■	■	31.65	7.99	2.70	10470	8045
10.00-20	7.50-20	■	■	39.76	10.00	3.21	13230	11025
10.00-20	8.00-20	■	■	39.76	10.00	3.21	13230	11025

---

### WELL BALANCED RUBBER COMPOUND

- Operate in low intensity applications and offer the lowest operating cost

### AGGRESSIVE DEEP TREAD DESIGN

- Provide great traction and stability



### EXCEPTIONAL TREAD RUBBER COMPOUND PROPERTIES

- Make this tire the longest lasting tire in the industry for low intensity applications\*

### STEEL BEAD REINFORCED HEEL

- Prevents rim slip

### WEAR INDICATOR

- Ensures maximum tire utilization

\* Based on internal testing

#### Remarks

(1) Check rim for size, especially on width, as this should correspond to tirebase marking. Check also max. load of rim with rim manufacturer, as wheel load will be restricted by lowest load capacity, either the one given by the rim or by the tire.

(2) The speeds quoted in the table are the maximum speeds of the unloaded vehicle. An increase in load capacity for lower speeds is not permitted. Loads apply to cyclic service applications. Cyclic service means applications where there is a variation in load and/or speed.

For further details, please consult the technical department.

Loads are valid for intermittent service only. Intermittent service means a minimum load variation of 2.5. Does not include the additional weight of the solid tire when converting from pneumatics.

**This document contains technical data of all products globally.**

**It is possible that certain items are not sold in your region.**

**Please contact your local sales contact to check tire availability in your region.**

AUTHORIZED DISTRIBUTOR:



Camso is the best of Camoplast and Solideal.  
To keep moving forward while staying true to our history,  
we're now the Road Free company.

[camsso.co](http://camsso.co)



FORMERLY  
CAMOPLAST  
SOLIDEAL