



HK 458 (E-4/L-4)

- A new, deep-tread, directional, pattern designed to provide greater traction for the most extreme wheel loader conditions
- Premium tread compound resistant to chunking/tearing paired to a high-stability lug design
- The proven cavity shape protects the sidewall throughout the footprint and fits on the standard OTR rim
- Steel belted construction provides maximum penetration resistance



APPLICATIONS:
WHEEL LOADER, LOGGING SERVICE

HK 458 (E-4/L-4)

Tire Size	Compound Construction	Catalog Number	Industry Code	Load/Speed Index	Load Rating	Recom'd Rim	Outside Diameter (in)	Overall Width (in)	Static Loaded Width (in)	Static Loaded Radius (in)	Flat Plate Area (in ²)	Tread Depth (32nd in)	Rated Load @ Inflation (lbs @ psi)	Weight (lbs)
20.5-25	Steel	6HK921	E-4	170B	20	17.00 / 2.0	57.9	21.5	N/A	N/A	N/A	64	13,200 @ 47	466
			L-4	186A2			58.1	21.7	N/A	N/A	N/A		20,900 @ 65	
23.5-25	Steel	6HK923	E-4	177B	20	19.50 / 2.5	63.3	25.0	N/A	N/A	N/A	68	16,100 @ 44	571
			L-4	191A2			63.4	25.1	N/A	N/A	N/A		24,000 @ 54	

N/A – not available currently

CONTACT YOUR TITAN REPRESENTATIVE TODAY FOR DETAILS.

1.800.872.2327 | www.titan-intl.com

01202021 © 2021 Titan International, Inc. TWI, Quincy, IL. All Rights Reserved. Materials and specifications are subject to change without notice. Goodyear is a registered trademark of Titan Goodyear Tire and Rubber Company.