LOGGER LUG III FLOTATION (HF-4/HF-3+)



- Extra-wide tread for high flotation in wet terrain while providing low ground penetration to minimize environmental impact
- Special forestry compound for increased resistance to tread chunking and tearing
- Four steel belted construction provides excellent penetration resistance





LOGGER LUG III FLOTATION (HF-4/HF-3+)														
Tire Size	Catalog Number	TL/ TT	Industry Code	Load/ Speed Index	Load Rating	Recom'd Rim	Outside Diameter (in)	Overall Width (in)	Static Loaded Width (in)	Static Loaded Radius (in)	Flat Plate Area (in ²)	Tread Depth (32nd in)	Rated Load @ Inflation (lbs @ psi)	Weight (lbs)
66X43.00-25NHS	YL39F3	TL	HF-4	174B 190A2	20 20	36.0TH	69.4 69.4	41.2 41.2	41.5 41.5	32.9 32.9	N/A N/A	112	14,800 @ 50 23,400 @ 50	1,512
66X43.00-26NHS	YL39F6	TL	HF-4	174B 190A2	20 20	DW36B	69.4 69.4	41.2 41.2	41.5 41.5	32.9 32.9	N/A N/A	112	14,800 @ 50 23,400 @ 50	1,505
67X34.00-25NHS	YL33R3	TL	HF-4	170B 186A2	14 14	30.0TH	69.2 69.2	34.3 34.3	34.7 35.2	32.4 31.4	420 580	118	13,200 @ 40 20,900 @ 40	1,361
67X34.00-26NHS	YL3R65	TL	HF-4	170B 186A2	14 14	DW30B	69.2 69.2	34.3 34.3	34.7 35.2	32.4 31.4	420 580	118	13,200 @ 40 20,900 @ 40	1,361
DH73X44.00-32	YL39R6	TL	HF-3+	180B 196A2	20 20	DH36	74.2 N/A	41.8 N/A	41.9 N/A	35.4 N/A	504 N/A	104	17,600 @ 50 27,600 @ 50	1,615
DH73X50.00-32	YL35V6	TL	HF-3+	174B 190A2	16 16	DH44	74.4 74.4	49.1 49.1	49.2 N/A	36.8 N/A	647 N/A	104	14,800 @ 35 23,400 @ 35	1,957
DH73X50.00-32	YL39V6	TL	HF-3+	179B 195A2	20 20	DH44	74.4 74.4	49.1 49.1	49.2 N/A	36.8 N/A	647 N/A	104	17,100 @ 45 26,800 @ 45	1,931

N/A - not available currently





1.800.872.2327 | www.titan-intl.com

02112021 © 2021 Titan International, Inc. TWI, Quincy, IL. All Rights Reserved. Materials and specifications are subject to change without notice. Goodyear is a registered trademark of Titan Goodyear Tire and Rubber Company.