



LOGGER LUG III (LS-2)

- Optimal lug angle provides optimized balance between traction and cut resistance
- Special forestry compound for increased resistance to tread chunking and tearing
- Steel belt construction provides excellent penetration resistance



APPLICATIONS: LOGGING SERVICE

LOGGER LUG III (LS-2)

Tire Size	Catalog Number	Industry Code	Load/Speed Index	Load Rating	Recom'd Rim	Outside Diameter (in)	Overall Width (in)	Static Loaded Width (in)	Static Loaded Radius (in)	Flat Plate Area (in ²)	Tread Depth (32nd in)	Rated Load @ Inflation (lbs @ psi)	Weight (lbs)
18.4-26	LL3056	LS-2	141A6	10	DW16A	58.2	18.4	19.8	26.7	N/A	63	5,680 @ 25	386
			153A2	10		58.2	18.4	19.8	26.7	N/A		8,050 @ 30	
18.4-34	LL3054	LS-2	145A6	10	DW16A	65.7	18.4	19.8	29.9	N/A	63	6,400 @ 25	451
			157A2	10		65.7	18.4	19.8	29.9	N/A		9,100 @ 30	
23.1-26	YL3586	LS-2	160A6	16	DW20B	63.8	24.2	25.4	29.5	302	72	9,900 @ 35	628
			172A2	16		63.8	24.2	26.1	28.7	N/A		13,900 @ 40	
24.5-32	YL3599	LS-2	164A6	16	DH21	70.3	24.3	25.2	32.7	350	64	11,000 @ 30	771
			175A2	16		70.3	24.4	25.7	32.2	418		15,200 @ 35	

N/A – not available currently

CONTACT YOUR TITAN REPRESENTATIVE TODAY FOR DETAILS.



1.800.872.2327 | www.titan-intl.com

02112021 © 2021 Titan International, Inc. TWI, Quincy, IL. All Rights Reserved. Materials and specifications are subject to change without notice. Goodyear is a registered trademark of Titan Goodyear Tire and Rubber Company.